



MULTIFUNCTIONAL AND COMPACT STOCKPILE CONVEYOR

Applications

The Transporter 4030E mobile wheeled stockpile conveyor is designed to process stones, aggregate, minerals, solid waste, topsoil, compost and green waste type products.

Benefits and advantages

- Steady and smooth operation, powered by electric motor
- Robust, heavy duty construction allows a wide variety of materials to be transported
- Simple structure
- Maintenance friendly with full service accessibility and central grease points
- · Adjustable height
- · Simple and quick installation
- Radial wheels
- · Polyurethane scraper
- 5990 mm stockpile height
- Capacity up to 200 TPH
- · Minimal set-up time

Optional

- Conveyor length range from 6000 mm until 24000 mm
- Conveyor belt width from 500 mm until 1200 mm
- · Hydraulic cylinder to adjust height
- · Hydraulic motor instead of electric motor

Dimensions

 Gross weight
 1500 (kg)

 Length
 12000 (mm)

 Working width
 2510 (mm)

 Height (max.)
 6090 (mm)

 Transport length
 12000 (mm)

 Transport width
 1290 (mm)

 Transport height
 865 (mm)

Power unit

Powered byElectric motorPower5.5kW

Conveyor

 Length
 12000 (mm)

 Width
 750 (mm)


 Type
 EP400 3 ply conveyor belt



Radial wheels



Electric motor



Polyurethane scraper



Central grease points

